

## WHEELS

Product group	Wheels
Item number	59911630
Valid wheel size	10.0 / 75 - 15.3
Brand	BKT
Tread pattern	AS 504
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+40
Rim colour	Silver
Load capacity complete wheel [kg]	1550
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15711750
LI / SI / PR	111 A8 / 123 A8, 10 PR
Load capacity 1 [kg]	1090
Speed 1 [km/h].	40
Load capacity 2 [kg]	1550
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	35,97

ECE regulation number	ECE 106
Section width (mm)	264
Stat. radius (SLR) [mm]	360
Rolling circumference [mm].	2404
Tread depth (mm)	23,0
E-Ready	No
Assembly Item no. Rim	• 32010180
Load capacity of rim 1 [kg]	3075
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2725
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,90
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No

---

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade