

WHEELS

Product group	Wheels
Item number	59911633
Valid wheel size	10.0 / 75 - 15.3
Brand	Alliance
Tread pattern	320 Value Plus
Valid rim size	9.00 x 15.3
Rim connection	5/66.5/112
Bolt hole design	B1
Offset (mm)	+40
Rim colour	Silver
Load capacity complete wheel [kg]	1850
Speed complete wheel [km/h]	30
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15211615
LI / SI / PR	129 A6 / 125 A8, 10 PR
Load capacity 1 [kg]	1850
Speed 1 [km/h].	30
Load capacity 2 [kg]	1650
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	30,12

ECE regulation number	ECE 106
Section width (mm)	264
Stat. radius (SLR) [mm]	343
Rolling circumference [mm].	2243
Tread depth (mm)	8,0
E-Ready	No
Assembly Item no. Rim	• 10000948
Load capacity of rim 1 [kg]	2750
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,30
Number of bolt holes	5
hub hole diameter [mm].	66.5
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	8.0
Ventilation holes	No

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade