

WHEELS

Product group	Wheels
Item number	59911675
Valid wheel size	11.5 / 80 - 15.3
Brand	Alliance
Tread pattern	320 Value Plus
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	E2
Offset (mm)	-5
Rim colour	Silver
Load capacity complete wheel [kg]	2900
Speed complete wheel [km/h]	30



Technical Informations

Assembly Item no. Tyres	• 15211631
LI / SI / PR	145 A6 / 141 A8, 14 PR
Load capacity 1 [kg]	2900
Speed 1 [km/h].	30
Load capacity 2 [kg]	2575
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	30,87
ECE regulation number	ECE 106
Section width (mm)	290

Stat. radius (SLR) [mm]	364.8
Speed Radius Index (SRI)	400
Rolling circumference [mm].	2540
Tread depth (mm)	9,0
E-Ready	No
Assembly Item no. Rim	• 31810195
Load capacity of rim 1 [kg]	2800
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2650
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,70
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161

Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade