

## WHEELS

|                                   |                 |
|-----------------------------------|-----------------|
| Product group                     | Wheels          |
| Item number                       | 59911680        |
| Valid wheel size                  | 400 / 60 - 15.5 |
| Brand                             | Alliance        |
| Tread pattern                     | FarmPRO 327     |
| Valid rim size                    | 13.00 x 15.5    |
| Rim connection                    | 6/161/205       |
| Bolt hole design                  | A2              |
| Offset (mm)                       | -15             |
| Rim colour                        | Silver          |
| Load capacity complete wheel [kg] | 2900            |
| Speed complete wheel [km/h]       | 40              |



## Technical Informations

|                            |                        |
|----------------------------|------------------------|
| Assembly Item no. Tyres    | • 15211653             |
| LI / SI / PR               | 132 A8 / 145 A8, 14 PR |
| Load capacity 1 [kg]       | 2000                   |
| Speed 1 [km/h].            | 40                     |
| Load capacity 2 [kg]       | 2900                   |
| Speed 2 [km/h].            | 40                     |
| Antistatic                 | No                     |
| Tyre colour                | Black                  |
| Nettogewicht [kg] (gültig) | 60,37                  |
| ECE regulation number      | ECE 106                |
| Section width (mm)         | 405                    |

|                                |                               |
|--------------------------------|-------------------------------|
| Stat. radius (SLR) [mm]        | 375                           |
| Rolling circumference [mm].    | 2498                          |
| Tread depth (mm)               | 13,1                          |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 32010300                    |
| Load capacity of rim 1 [kg]    | 4500                          |
| Speed Rims 1 [km/h]            | 25                            |
| Load capacity of rim 2 [kg]    | 3750                          |
| Speed Rims 2 [km/h]            | 40                            |
| Maximum speed [km/h].          | 40                            |
| Maximum air pressure [bar].    | 3,60                          |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | kein Hump                     |
| Valve protection               | VS H                          |
| Single / multi-part            | einteilig                     |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Cavity Sealed                  | No                            |
| Ventilation holes              | No                            |
| Verschweißung beidseitig       | No                            |
| Rim centering                  | BC                            |
| Number of bolt holes           | 6                             |
| Bolt hole diameter [mm]        | 21.5                          |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R16                           |
| hub hole diameter [mm].        | 161                           |
| Bolt hole circle diameter [mm] | 205                           |

---

|                          |                |
|--------------------------|----------------|
| Valve seat               | External Valve |
| Valve hole diameter [mm] | 15.7           |
| Preassembled valve       | No             |
| Valve design             | Rubber valve   |
| Valve designation ETRTO  | V2.03.3        |
| Valve length [mm]        | 43.0           |
| Valve angle [°]          | gerade         |