

## WHEELS

Product group	Wheels
Item number	59911710
Valid wheel size	15.0 / 55 - 17
Brand	Alliance
Tread pattern	320 Value Plus
Valid rim size	13.00 x 17
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2575
Speed complete wheel [km/h]	30



## Technical Informations

Assembly Item no. Tyres	• 15211687
LI / SI / PR	141 A6 / 138 A8, 14 PR
Load capacity 1 [kg]	2575
Speed 1 [km/h].	30
Load capacity 2 [kg]	2360
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	51,81
ECE regulation number	ECE 106
Section width (mm)	391

Stat. radius (SLR) [mm]	372
Rolling circumference [mm].	2490
Tread depth (mm)	11,5
E-Ready	No
Assembly Item no. Rim	• 33060081
Load capacity of rim 1 [kg]	4950
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4150
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,70
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve

---

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade