

WHEELS

Product group	Wheels
Item number	59911712
Valid wheel size	15.0 / 55 - 17
Brand	Alliance
Tread pattern	320 Value Plus
Valid rim size	13.00 x 17
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2575
Speed complete wheel [km/h]	30





Technical Informations

Assembly Item no. Tyres	15211687
LI / SI / PR	141 A6 / 138 A8, 14 PR
Load capacity 1 [kg]	2575
Speed 1 [km/h].	30
Load capacity 2 [kg]	2360
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	50,91
ECE regulation number	ECE 106
Section width (mm)	391

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Stat. radius (SLR) [mm]	372
Rolling circumference [mm].	2490
Tread depth (mm)	11,5
E-Ready	No
Assembly Item no. Rim	32010315
Load capacity of rim 1 [kg]	3300
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,70
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.





Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade