

## WHEELS

Product group	Wheels
Item number	59911714
Valid wheel size	500 / 55 - 17
Brand	Alliance
Tread pattern	Forestry 328
Valid rim size	16.00 x 17
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Red
Load capacity complete wheel [kg]	3875
Speed complete wheel [km/h]	10



## Technical Informations

Assembly Item no. Tyres	• 15211701
LI / SI / PR	155 A2 / 148 A8, 12 PR
Load capacity 1 [kg]	3875
Speed 1 [km/h].	10
Load capacity 2 [kg]	3150
Speed 2 [km/h].	40
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	99,01
ECE regulation number	ECE 106

Section width (mm)	503
Stat. radius (SLR) [mm]	441
Rolling circumference [mm].	2906
Tyre capacity 75% [ltr.]	160.5
E-Ready	No
Assembly Item no. Rim	• 30810333
Load capacity of rim 1 [kg]	4250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3250
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,30
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL3000
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161

---

<b>Bolt hole circle diameter [mm]</b>	205
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade