

## WHEELS

Product group	Wheels
Item number	59911716
Valid wheel size	500 / 55 - 20
Brand	Alliance
Tread pattern	FarmPRO 327
Valid rim size	16 x 20
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	3875
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15212559
LI / SI / PR	143 A8 / 155 A8, 12 PR
Load capacity 1 [kg]	2725
Speed 1 [km/h].	40
Load capacity 2 [kg]	3875
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	108,27
ECE regulation number	ECE 106
Section width (mm)	503

Stat. radius (SLR) [mm]	464
Rolling circumference [mm].	3063
Tread depth (mm)	13,5
E-Ready	No
Assembly Item no. Rim	• 31610601
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,25
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7

---

Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade