

## WHEELS

|                                   |               |
|-----------------------------------|---------------|
| Product group                     | Wheels        |
| Item number                       | 59911719      |
| Valid wheel size                  | 500 / 50 - 17 |
| Brand                             | Alliance      |
| Tread pattern                     | FarmPRO 327   |
| Valid rim size                    | 16.00 x 17    |
| Rim connection                    | 6/161/205     |
| Bolt hole design                  | A2            |
| Offset (mm)                       | -35           |
| Rim colour                        | Silver        |
| Load capacity complete wheel [kg] | 3750          |
| Speed complete wheel [km/h]       | 40            |



## Technical Informations

|                            |                        |
|----------------------------|------------------------|
| Assembly Item no. Tyres    | • 15211695             |
| LI / SI / PR               | 141 A8 / 154 A8, 18 PR |
| Load capacity 1 [kg]       | 2575                   |
| Speed 1 [km/h].            | 40                     |
| Load capacity 2 [kg]       | 3750                   |
| Antistatic                 | No                     |
| Tyre colour                | Black                  |
| Nettogewicht [kg] (gültig) | 90,05                  |
| ECE regulation number      | ECE 106                |
| Section width (mm)         | 500                    |
| Stat. radius (SLR) [mm]    | 435                    |

|                                |                  |
|--------------------------------|------------------|
| Rolling circumference [mm].    | 2840             |
| E-Ready                        | No               |
| Assembly Item no. Rim          | • 31610334       |
| Load capacity of rim 1 [kg]    | 4420             |
| Speed Rims 1 [km/h]            | 40               |
| Load capacity of rim 2 [kg]    | 3250             |
| Speed Rims 2 [km/h]            | 65               |
| Maximum speed [km/h].          | 40               |
| Maximum air pressure [bar].    | 3,50             |
| Type of drive                  | Towed axle       |
| Hump                           | kein Hump        |
| Valve protection               | VS H             |
| Single / multi-part            | einteilig        |
| Rim material                   | steel            |
| RAL                            | RAL9006          |
| Cavity Sealed                  | No               |
| Knurling                       | without knurling |
| Ventilation holes              | No               |
| Verschweißung beidseitig       | No               |
| Rim centering                  | BC               |
| Number of bolt holes           | 6                |
| Bolt hole diameter [mm]        | 21.5             |
| Countersinking                 | Sphere           |
| Spherical countersink [mm].    | R16              |
| hub hole diameter [mm].        | 161              |
| Bolt hole circle diameter [mm] | 205              |
| Valve seat                     | External Valve   |

---

|                          |             |
|--------------------------|-------------|
| Valve hole diameter [mm] | 15.7        |
| Preassembled valve       | No          |
| Valve design             | Metal valve |
| Valve designation ETRTO  | V5.01.1     |
| Valve length [mm]        | 50.0        |
| Valve angle [°]          | gerade      |