

WHEELS

Product group	Wheels
Item number	59911724
Valid wheel size	500 / 50 - 17
Brand	Alliance
Tread pattern	320 Value Plus
Valid rim size	16.00 x 17
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	3650
Speed complete wheel [km/h]	30



Technical Informations

Assembly Item no. Tyres	• 15211689
LI / SI / PR	153 A6 / 149 A8, 14 PR
Load capacity 1 [kg]	3650
Speed 1 [km/h].	30
Load capacity 2 [kg]	3250
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	76,71
ECE regulation number	ECE 106
Section width (mm)	500

Stat. radius (SLR) [mm]	424
Rolling circumference [mm].	2760
Tread depth (mm)	12,7
E-Ready	No
Assembly Item no. Rim	• 31610324
Load capacity of rim 1 [kg]	3750
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,80
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221

Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade