

WHEELS

Product group	Wheels
Item number	59911754
Valid wheel size	400 / 60 - 15.5
Brand	BKT
Tread pattern	TR 882
Valid rim size	13.00 x 15.5
Rim connection	6/161/205
Bolt hole design	E2
Rim colour	Silver
Load capacity complete wheel [kg]	2900
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711810
LI / SI / PR	133 A8 / 145 A8, 14 PR
Load capacity 1 [kg]	2060
Speed 1 [km/h].	40
Load capacity 2 [kg]	2900
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	59,80
ECE regulation number	ECE 106

Section width (mm)	400
Stat. radius (SLR) [mm]	378
Rolling circumference [mm].	2605
Tread depth (mm)	20,0
E-Ready	No
Assembly Item no. Rim	• 32010304
Load capacity of rim 1 [kg]	3875
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3500
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,60
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade