

WHEELS

| | |
|-----------------------------------|---------------|
| Product group | Wheels |
| Item number | 59911771 |
| Valid wheel size | 500 / 50 R 17 |
| Brand | Alliance |
| Tread pattern | 882 |
| Valid rim size | 16.00 x 17 |
| Rim connection | 6/161/205 |
| Bolt hole design | A2 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 3250 |
| Speed complete wheel [km/h] | 65 |



Technical Informations

| | |
|-----------------------------|------------|
| Assembly Item no. Tyres | • 15215505 |
| LI / SI / PR | 149 D |
| Load capacity 1 [kg] | 3250 |
| Speed 1 [km/h]. | 65 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 91,65 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 503 |
| Stat. radius (SLR) [mm] | 409 |
| Rolling circumference [mm]. | 2833 |

| | |
|--------------------------------|----------------|
| Tread depth (mm) | 15,0 |
| Tyre capacity 75% [ltr.] | 145.5 |
| E-Ready | No |
| Assembly Item no. Rim | • 31610333 |
| Load capacity of rim 1 [kg] | 4420 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 3250 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 65 |
| Maximum air pressure [bar]. | 5,00 |
| Type of drive | Towed axle |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 6 |
| Bolt hole diameter [mm] | 21.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |

| | |
|-------------------------|-------------|
| Preassembled valve | No |
| Valve design | Metal valve |
| Valve designation ETRTO | V5.01.1 |
| Valve length [mm] | 50.0 |
| Valve angle [°] | gerade |