

## WHEELS

|                                   |                    |
|-----------------------------------|--------------------|
| Product group                     | Wheels             |
| Item number                       | 59911775           |
| Valid wheel size                  | 500 / 60 - 22.5    |
| Brand                             | Alliance           |
| Tread pattern                     | 328 Value Plus     |
| Valid rim size                    | AG 16.00 x 22.5 H2 |
| Rim connection                    | 10/281/335         |
| Bolt hole design                  | A3                 |
| Rim colour                        | Silver             |
| Load capacity complete wheel [kg] | 3450               |
| Speed complete wheel [km/h]       | 40                 |



## Technical Informations

|                            |                        |
|----------------------------|------------------------|
| Assembly Item no. Tyres    | • 15212602             |
| LI / SI / PR               | 151 A8 / 163 A8, 16 PR |
| Load capacity 1 [kg]       | 3450                   |
| Speed 1 [km/h].            | 40                     |
| Load capacity 2 [kg]       | 4875                   |
| Speed 2 [km/h].            | 40                     |
| Antistatic                 | No                     |
| Tyre colour                | Black                  |
| Nettogewicht [kg] (gültig) | 121,65                 |
| ECE regulation number      | ECE 106                |
| Section width (mm)         | 500                    |

|                             |                               |
|-----------------------------|-------------------------------|
| Stat. radius (SLR) [mm]     | 510                           |
| Rolling circumference [mm]. | 3460                          |
| Tread depth (mm)            | 26,0                          |
| Number of lugs              | 28x2                          |
| E-Ready                     | No                            |
| Assembly Item no. Rim       | • 33060354                    |
| Load capacity of rim 1 [kg] | 7600                          |
| Speed Rims 1 [km/h]         | 40                            |
| Load capacity of rim 2 [kg] | 5600                          |
| Speed Rims 2 [km/h]         | 65                            |
| Maximum speed [km/h].       | 40                            |
| Maximum air pressure [bar]. | 3,20                          |
| Type of drive               | Angetriebene & gezogene Achse |
| Hump                        | H2                            |
| Valve protection            | VS H                          |
| Single / multi-part         | einteilig                     |
| Rim material                | steel                         |
| RAL                         | RAL9006                       |
| Cavity Sealed               | No                            |
| Ventilation holes           | No                            |
| Verschweißung beidseitig    | No                            |
| Rim centering               | BC                            |
| Number of bolt holes        | 10                            |
| Bolt hole design EUWA       | B22 ES 36                     |
| Bolt hole diameter [mm]     | 27                            |
| Countersinking              | Sphere                        |
| Spherical countersink [mm]. | R18                           |

---

|                                |                |
|--------------------------------|----------------|
| hub hole diameter [mm].        | 281            |
| Bolt hole circle diameter [mm] | 335            |
| Valve seat                     | External Valve |
| Valve hole diameter [mm]       | 15.7           |
| Preassembled valve             | No             |
| Valve design                   | Metal valve    |
| Valve designation ETRTO        | V5.01.1        |
| Valve length [mm]              | 50.0           |
| Valve angle [°]                | gerade         |