

WHEELS

| | |
|-----------------------------------|--------------------|
| Product group | Wheels |
| Item number | 59911776 |
| Valid wheel size | 500 / 60 - 22.5 |
| Brand | Alliance |
| Tread pattern | 328 Value Plus |
| Valid rim size | AG 16.00 x 22.5 H2 |
| Rim connection | 8/221/275 |
| Bolt hole design | A3 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 3450 |
| Speed complete wheel [km/h] | 40 |



Technical Informations

| | |
|----------------------------|------------------------|
| Assembly Item no. Tyres | • 15212602 |
| LI / SI / PR | 151 A8 / 163 A8, 16 PR |
| Load capacity 1 [kg] | 3450 |
| Speed 1 [km/h]. | 40 |
| Load capacity 2 [kg] | 4875 |
| Speed 2 [km/h]. | 40 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 123,65 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 500 |

| | |
|-----------------------------|------------|
| Stat. radius (SLR) [mm] | 510 |
| Rolling circumference [mm]. | 3460 |
| Tread depth (mm) | 26,0 |
| Number of lugs | 28x2 |
| E-Ready | No |
| Assembly Item no. Rim | • 33060358 |
| Load capacity of rim 1 [kg] | 7250 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 5300 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 40 |
| Maximum air pressure [bar]. | 3,20 |
| Hump | H2 |
| Valve protection | VS H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 8 |
| Bolt hole design EUWA | B22 ES 36 |
| Bolt hole diameter [mm] | 27 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| hub hole diameter [mm]. | 221 |

| | |
|---------------------------------------|----------------|
| Bolt hole circle diameter [mm] | 275 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |
| Valve design | Metal valve |
| Valve designation ETRTO | V5.01.1 |
| Valve length [mm] | 50.0 |
| Valve angle [°] | gerade |