

WHEELS

Product group	Wheels
Item number	59911830
Valid wheel size	5.00 - 15
Brand	BKT
Tread pattern	AS 504
Valid rim size	4 J x 15 H
Rim connection	5/110/160
Bolt hole design	A1
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	600
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711680
LI / SI / PR	75 A8 / 88 A8, 6 PR
Load capacity 1 [kg]	387
Speed 1 [km/h].	40
Load capacity 2 [kg]	560
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	15,03

ECE regulation number	ECE 106
Section width (mm)	140
Stat. radius (SLR) [mm]	308
Rolling circumference [mm].	1957
Tread depth (mm)	16,0
Number of lugs	16x2
E-Ready	No
Assembly Item no. Rim	• 31610053
Load capacity of rim 1 [kg]	750
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,50
Number of bolt holes	5
Bolt hole design EUWA	B14 ES 28
hub hole diameter [mm].	110
Bolt hole circle diameter [mm]	160
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Type of drive	Towed axle
Hump	H
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No