

WHEELS

Product group	Wheels
Item number	59911868
Valid wheel size	6.00 - 16
Brand	BKT
Tread pattern	AS 504
Valid rim size	4.50 E x 16
Rim connection	5/66.6/112
Bolt hole design	E1
Rim colour	Silver
Load capacity complete wheel [kg]	750
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15711823
LI / SI / PR	83 A8 / 95 A8, 6 PR
Load capacity 1 [kg]	487
Speed 1 [km/h].	40
Load capacity 2 [kg]	690
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	21,18
ECE regulation number	ECE 106
Section width (mm)	164

Stat. radius (SLR) [mm]	343
Rolling circumference [mm].	2190
Tread depth (mm)	18,0
Number of lugs	20x2
E-Ready	No
Assembly Item no. Rim	• 31410187
Load capacity of rim 1 [kg]	825
Speed Rims 1 [km/h]	30
Load capacity of rim 2 [kg]	750
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,80
Number of bolt holes	5
hub hole diameter [mm].	66.6
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No