

WHEELS

Product group	Wheels
Item number	59911869
Valid wheel size	5.50 - 16
Brand	BKT
Tread pattern	TF 9090
Valid rim size	4.50 E x 16
Rim connection	5/94/140
Bolt hole design	E1
Offset (mm)	+25
Rim colour	Silver
Load capacity complete wheel [kg]	425
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15721055
LI / SI / PR	86 A6 / 78 A8, 6 PR
Load capacity 1 [kg]	530
Speed 1 [km/h].	30
Load capacity 2 [kg]	425
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	20,70

ECE regulation number	ECE 106
Section width (mm)	150
Stat. radius (SLR) [mm]	332
Rolling circumference [mm].	2116
Tread depth (mm)	13,0
E-Ready	No
Assembly Item no. Rim	• 31610184
Load capacity of rim 1 [kg]	760
Speed Rims 1 [km/h]	15
Load capacity of rim 2 [kg]	425
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,70
Number of bolt holes	5
hub hole diameter [mm].	94
Bolt hole circle diameter [mm]	140
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No

Verschweißung beidseitig	No
Valve seat	External Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No