

## WHEELS

Product group	Wheels
Item number	59911925
Valid wheel size	7.50 - 16
Brand	BKT
Tread pattern	AS 504
Valid rim size	5.50 F x 16
Rim connection	6/161/205
Bolt hole design	E2
Rim colour	Silver
Load capacity complete wheel [kg]	1120
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15711828
LI / SI / PR	99 A8 / 112 A8, 8 PR
Load capacity 1 [kg]	750
Speed 1 [km/h].	40
Load capacity 2 [kg]	1120
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	24,53
ECE regulation number	ECE 106
Section width (mm)	209

Stat. radius (SLR) [mm]	372
Rolling circumference [mm].	2475
Tread depth (mm)	22,0
Number of lugs	19x2
E-Ready	No
Assembly Item no. Rim	• 31610075
Load capacity of rim 1 [kg]	1200
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,20
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Preassembled valve	No