

WHEELS

Product group	Wheels
Item number	59911970
Valid wheel size	13.0 / 75 - 16
Brand	BKT
Tread pattern	AW 702
Valid rim size	11 x 16
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2180
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15711836
LI / SI / PR	135 A8, 10 PR
Load capacity 1 [kg]	2180
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	50,16
ECE regulation number	ECE 106
Section width (mm)	340
Stat. radius (SLR) [mm]	396
Rolling circumference [mm].	2726

Tread depth (mm)	12,0
E-Ready	No
Assembly Item no. Rim	• 30012034
Load capacity of rim 1 [kg]	2520
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	3550
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,00
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0

Valve angle [°]

gerade
