

WHEELS

Product group	Wheels
Item number	59911993
Valid wheel size	340 / 55 - 16
Brand	BKT
Tread pattern	AW 729
Valid rim size	11 x 16
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2060
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15711817
LI / SI / PR	121 A8 / 133 A8
Load capacity 1 [kg]	1450
Speed 1 [km/h].	40
Load capacity 2 [kg]	2060
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	49,25
ECE regulation number	ECE 106
Section width (mm)	343

Stat. radius (SLR) [mm]	358
Rolling circumference [mm].	2358
Tread depth (mm)	13,5
E-Ready	No
Assembly Item no. Rim	• 30012034
Load capacity of rim 1 [kg]	2520
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	3550
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,20
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve

Valve length [mm]	55.0
Valve angle [°]	gerade
