

WHEELS

Product group	Wheels
Item number	59912074
Valid wheel size	VF 400 / 45 R 17.5
Brand	BKT
Tread pattern	Ridemax FL 693 M
Valid rim size	14.00 x 17.5
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15715080
LI / SI / PR	159 D
Load capacity 1 [kg]	4375
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	76,18
ECE regulation number	ECE 106
Section width (mm)	400

Stat. radius (SLR) [mm]	343
Speed Radius Index (SRI)	390
Rolling circumference [mm].	2357
Tread depth (mm)	11,5
E-Ready	No
Assembly Item no. Rim	• 33060111
Load capacity of rim 1 [kg]	6150
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	5200
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	65
Maximum air pressure [bar].	6,00
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade