

## WHEELS

Product group	Wheels
Item number	59912091
Valid wheel size	425 / 55 R 17
Brand	Alliance
Tread pattern	570
Valid rim size	13.00 x 17
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver



## Technical Informations

Assembly Item no. Tyres	• 15235122
LI / SI / PR	140 A8 / 140 B
Load capacity 1 [kg]	2500
Speed 1 [km/h].	40
Load capacity 2 [kg]	2500
Speed 2 [km/h].	50
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	79,21
ECE regulation number	ECE 106

Section width (mm)	425
Stat. radius (SLR) [mm]	400
Rolling circumference [mm].	2656
Tread depth (mm)	31,0
Number of lugs	17x2
E-Ready	No
Assembly Item no. Rim	• 33060081
Load capacity of rim 1 [kg]	4950
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4150
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,50
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161

---

<b>Bolt hole circle diameter [mm]</b>	205
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>Valve design</b>	Rubber valve
<b>Valve length [mm]</b>	55.0
<b>Valve angle [°]</b>	gerade