

## WHEELS

Product group	Wheels
Item number	59912095
Valid wheel size	425 / 55 R 17
Brand	Alliance
Tread pattern	570
Valid rim size	13.00 x 17
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+45
Rim colour	Silver
Load capacity complete wheel [kg]	2900
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15235122
LI / SI / PR	140 A8 / 140 B
Load capacity 1 [kg]	2500
Speed 1 [km/h].	40
Load capacity 2 [kg]	2500
Speed 2 [km/h].	50
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	79,35
ECE regulation number	ECE 106

Section width (mm)	425
Stat. radius (SLR) [mm]	400
Rolling circumference [mm].	2656
Tread depth (mm)	31,0
Number of lugs	17x2
E-Ready	No
Assembly Item no. Rim	• 32010312
Load capacity of rim 1 [kg]	3350
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	3,50
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve

---

Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade