

WHEELS

Product group	Wheels
Item number	59912178
Valid wheel size	15.0 / 55 - 17
Brand	BKT
Tread pattern	AW 705
Valid rim size	13.00 x 17
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2575
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	58,27
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711847
LI / SI / PR	141 A8, 14 PR
Load capacity 1 [kg]	2575
Speed 1 [km/h].	40
Maximum air pressure [bar].	3,70
TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No

ECE regulation number	ECE 106
Section width (mm)	381
Stat. radius (SLR) [mm]	391
Speed Radius Index (SRI)	410
Rolling circumference [mm].	2575
Tread depth (mm)	12,0
Assembly Item no. Rim	• 32010315
Load capacity of rim 1 [kg]	3300
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 ES 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No
Verschweißung beidseitig	No

Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7