

WHEELS

Product group	Wheels
Item number	59912182
Valid wheel size	15.0 / 55 - 17
Brand	BKT
Tread pattern	AW 705
Valid rim size	13.00 x 17
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2575
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15711847
LI / SI / PR	141 A8, 14 PR
Load capacity 1 [kg]	2575
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	56,54
ECE regulation number	ECE 106
Section width (mm)	381
Stat. radius (SLR) [mm]	391
Speed Radius Index (SRI)	410

Rolling circumference [mm].	2575
Tread depth (mm)	12,0
E-Ready	No
Assembly Item no. Rim	• 33060081
Load capacity of rim 1 [kg]	4950
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4150
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,70
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7

Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade