

WHEELS

Product group	Wheels
Item number	59912201
Valid wheel size	15.0 / 55 - 17
Brand	BKT
Tread pattern	AW 729
Valid rim size	13.00 x 17
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	1500
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711853
LI / SI / PR	122 A8 / 134 A8, 10 PR
Load capacity 1 [kg]	1500
Speed 1 [km/h].	40
Load capacity 2 [kg]	2120
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	56,11
ECE regulation number	ECE 106

Section width (mm)	385
Stat. radius (SLR) [mm]	377
Rolling circumference [mm].	2560
Tread depth (mm)	12,0
E-Ready	No
Assembly Item no. Rim	• 33060109
Load capacity of rim 1 [kg]	3800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2800
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,60
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade