

WHEELS

Product group	Wheels
Item number	59912236
Valid wheel size	500 / 50 - 17
Brand	BKT
Tread pattern	AW 708
Valid rim size	16.00 x 17 H2
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	3550
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15712436
LI / SI / PR	149 A8, 14 PR
Load capacity 1 [kg]	3250
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	92,56
ECE regulation number	ECE 106
Section width (mm)	500
Stat. radius (SLR) [mm]	416
Rolling circumference [mm].	2750

Tread depth (mm)	12,0
E-Ready	No
Assembly Item no. Rim	• 30810380
Load capacity of rim 1 [kg]	5800
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3750
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,80
Type of drive	Angetriebene & gezogene Achse
Hump	H2
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7

Preassembled valve

No
