

WHEELS

Product group	Wheels
Item number	59912299
Valid wheel size	500 / 50 - 17
Brand	BKT
Tread pattern	AW 708
Valid rim size	16.00 x 17
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	3250
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15712436
LI / SI / PR	149 A8, 14 PR
Load capacity 1 [kg]	3250
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	88,00
ECE regulation number	ECE 106
Section width (mm)	500
Stat. radius (SLR) [mm]	416

Rolling circumference [mm].	2750
Tread depth (mm)	12,0
E-Ready	No
Assembly Item no. Rim	• 33060099
Load capacity of rim 1 [kg]	4900
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4150
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,80
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade