

## WHEELS

Product group	Wheels
Item number	59912336
Valid wheel size	VF 480 / 45 R 17
Brand	BKT
Tread pattern	AW 711
Valid rim size	16.00 x 17
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-35
Rim colour	Silver
Load capacity complete wheel [kg]	4420
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15717225
LI / SI / PR	167 A8 / 167 B
Load capacity 1 [kg]	5450
Speed 1 [km/h].	40
Load capacity 2 [kg]	5450
Speed 2 [km/h].	50
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	87,10
ECE regulation number	ECE 106
Section width (mm)	491
Stat. radius (SLR) [mm]	363
Rolling circumference [mm].	2644
E-Ready	No
Assembly Item no. Rim	• 31610334
Load capacity of rim 1 [kg]	4420
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3250
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,00
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

---

<b>Knurling</b>	without knurling
<b>Ventilation holes</b>	No
<b>Verschweißung beidseitig</b>	No
<b>Valve seat</b>	External Valve
<b>Valve hole diameter [mm]</b>	15.7
<b>Preassembled valve</b>	No
<b>TPMS-kompatibles Ventil</b>	No
<b>Valve design</b>	Metal valve
<b>Valve designation ETRTO</b>	V5.01.1
<b>Valve length [mm]</b>	50.0
<b>Valve angle [°]</b>	gerade