

## WHEELS

|                                   |                |
|-----------------------------------|----------------|
| Product group                     | Wheels         |
| Item number                       | 59912359       |
| Valid wheel size                  | 19.0 / 45 - 17 |
| Brand                             | BKT            |
| Tread pattern                     | AS 504         |
| Valid rim size                    | 16.00 x 17     |
| Rim connection                    | 8/221/275      |
| Bolt hole design                  | A2             |
| Offset (mm)                       | -35            |
| Rim colour                        | Silver         |
| Load capacity complete wheel [kg] | 3000           |
| Speed complete wheel [km/h]       | 40             |
| RDRA (Reifendruckregelanlage)     | No             |
| RDKS (Reifendruckkontrollsystem)  | No             |



## Technical Informations

|                            |                        |
|----------------------------|------------------------|
| Assembly Item no. Tyres    | • 15712420             |
| LI / SI / PR               | 131 A8 / 144 A8, 14 PR |
| Load capacity 1 [kg]       | 1950                   |
| Speed 1 [km/h].            | 40                     |
| Load capacity 2 [kg]       | 2800                   |
| Speed 2 [km/h].            | 40                     |
| Antistatic                 | No                     |
| Tyre colour                | Black                  |
| Nettogewicht [kg] (gültig) | 73,45                  |

|                                |            |
|--------------------------------|------------|
| ECE regulation number          | ECE 106    |
| Section width (mm)             | 465        |
| Stat. radius (SLR) [mm]        | 389        |
| Rolling circumference [mm].    | 2578       |
| Tread depth (mm)               | 25,0       |
| E-Ready                        | No         |
| Assembly Item no. Rim          | • 31610326 |
| Load capacity of rim 1 [kg]    | 4420       |
| Speed Rims 1 [km/h]            | 40         |
| Load capacity of rim 2 [kg]    | 3250       |
| Speed Rims 2 [km/h]            | 65         |
| Maximum speed [km/h].          | 40         |
| Maximum air pressure [bar].    | 2,80       |
| Number of bolt holes           | 8          |
| hub hole diameter [mm].        | 221        |
| Bolt hole circle diameter [mm] | 275        |
| Bolt hole diameter [mm]        | 21.5       |
| Countersinking                 | Sphere     |
| Spherical countersink [mm].    | R16        |
| Type of drive                  | Towed axle |
| Hump                           | kein Hump  |
| Single / multi-part            | einteilig  |
| Rim centering                  | BC         |
| Rim material                   | steel      |
| RAL                            | RAL9006    |
| Cavity Sealed                  | No         |
| Ventilation holes              | No         |

---

|                          |                |
|--------------------------|----------------|
| Verschweißung beidseitig | No             |
| Valve seat               | External Valve |
| Valve hole diameter [mm] | 15.7           |
| Preassembled valve       | No             |
| TPMS-kompatibles Ventil  | No             |
| Valve design             | Rubber valve   |
| Valve designation ETRTO  | V2.03.3        |
| Valve length [mm]        | 43.0           |
| Valve angle [°]          | gerade         |