

WHEELS

| | |
|-----------------------------------|----------------|
| Product group | Wheels |
| Item number | 59912363 |
| Valid wheel size | 19.0 / 45 - 17 |
| Brand | BKT |
| Tread pattern | AS 504 |
| Valid rim size | 16.00 x 17 |
| Rim connection | 6/161/205 |
| Bolt hole design | A2 |
| Offset (mm) | -70 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 1950 |
| Speed complete wheel [km/h] | 40 |



Technical Informations

| | |
|----------------------------|------------------------|
| Assembly Item no. Tyres | • 15712420 |
| LI / SI / PR | 131 A8 / 144 A8, 14 PR |
| Load capacity 1 [kg] | 1950 |
| Speed 1 [km/h]. | 40 |
| Load capacity 2 [kg] | 2800 |
| Speed 2 [km/h]. | 40 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 73,05 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 465 |

| | |
|--------------------------------|-------------------------------|
| Stat. radius (SLR) [mm] | 389 |
| Rolling circumference [mm]. | 2578 |
| Tread depth (mm) | 25,0 |
| E-Ready | No |
| Assembly Item no. Rim | • 30810350 |
| Load capacity of rim 1 [kg] | 4000 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 3250 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 40 |
| Maximum air pressure [bar]. | 2,80 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 6 |
| Bolt hole diameter [mm] | 21.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Valve seat | External Valve |

| | |
|--------------------------|--------------|
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |
| Valve design | Rubber valve |
| Valve designation ETRTO | V2.03.3 |
| Valve length [mm] | 43.0 |
| Valve angle [°] | gerade |