

WHEELS

Product group	Wheels
Item number	59912364
Valid wheel size	19.0 / 45 - 17
Brand	BKT
Tread pattern	AS 504
Valid rim size	16.00 x 17
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-35
Rim colour	Silver
Load capacity complete wheel [kg]	2800
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15712420
LI / SI / PR	131 A8 / 144 A8, 14 PR
Load capacity 1 [kg]	1950
Speed 1 [km/h].	40
Load capacity 2 [kg]	2800
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	73,45
ECE regulation number	ECE 106
Section width (mm)	465

Stat. radius (SLR) [mm]	389
Rolling circumference [mm].	2578
Tread depth (mm)	25,0
E-Ready	No
Assembly Item no. Rim	• 31610334
Load capacity of rim 1 [kg]	4420
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3250
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	2,80
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161

Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade