

WHEELS

Product group	Wheels
Item number	59912398
Valid wheel size	10.5 / 80 - 18
Brand	BKT
Tread pattern	AS 504
Valid rim size	9 x 18
Rim connection	8/221/275
Bolt hole design	B3
Rim colour	Silver
Load capacity complete wheel [kg]	1950
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711870
LI / SI / PR	119 A8 / 131 A8, 10 PR
Load capacity 1 [kg]	1360
Speed 1 [km/h].	40
Load capacity 2 [kg]	1950
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	53,96
ECE regulation number	ECE 106

Section width (mm)	274
Stat. radius (SLR) [mm]	405
Rolling circumference [mm].	2657
Tread depth (mm)	22,0
E-Ready	No
Assembly Item no. Rim	• 32010139
Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,70
Number of bolt holes	8
Bolt hole design EUWA	B22 DS 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade