

WHEELS

Product group	Wheels
Item number	59912613
Valid wheel size	12.5 / 80 - 18
Brand	BKT
Tread pattern	AS 504
Valid rim size	11 x 18
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+75
Rim colour	Silver
Load capacity complete wheel [kg]	1850
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711930
LI / SI / PR	129 A8 / 142 A8, 12 PR
Load capacity 1 [kg]	1850
Speed 1 [km/h].	40
Load capacity 2 [kg]	2650
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	69,50

ECE regulation number	ECE 106
Section width (mm)	308
Stat. radius (SLR) [mm]	438
Rolling circumference [mm].	2892
Tread depth (mm)	28,0
E-Ready	No
Assembly Item no. Rim	• 31210182
Load capacity of rim 1 [kg]	3000
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,70
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade