

## WHEELS

|                                   |                |
|-----------------------------------|----------------|
| Product group                     | Wheels         |
| Item number                       | 59912641       |
| Valid wheel size                  | 12.5 / 80 - 18 |
| Brand                             | BKT            |
| Tread pattern                     | AW 702         |
| Valid rim size                    | 9 x 18         |
| Rim connection                    | 6/161/205      |
| Bolt hole design                  | A2             |
| Rim colour                        | Silver         |
| Load capacity complete wheel [kg] | 2650           |
| Speed complete wheel [km/h]       | 40             |
| Nettogewicht [kg] (gültig)        | 54,82          |
| RDRA (Reifendruckregelanlage)     | No             |
| RDKS (Reifendruckkontrollsystem)  | No             |



## Technical Informations

|                             |               |
|-----------------------------|---------------|
| Assembly Item no. Tyres     | • 15711880    |
| LI / SI / PR                | 142 A8, 12 PR |
| Load capacity 1 [kg]        | 2650          |
| Speed 1 [km/h].             | 40            |
| Maximum air pressure [bar]. | 5,00          |
| TL/TT                       | TL            |
| Tyre colour                 | Black         |
| E-Ready                     | No            |
| Antistatic                  | No            |

|                                |                               |
|--------------------------------|-------------------------------|
| ECE regulation number          | ECE 106                       |
| Section width (mm)             | 308                           |
| Stat. radius (SLR) [mm]        | 432                           |
| Rolling circumference [mm].    | 2827                          |
| Tread depth (mm)               | 12,0                          |
| Assembly Item no. Rim          | • 32010135                    |
| Load capacity of rim 1 [kg]    | 3350                          |
| Speed Rims 1 [km/h]            | 40                            |
| Load capacity of rim 2 [kg]    | 1800                          |
| Speed Rims 2 [km/h]            | 80                            |
| Maximum speed [km/h].          | 40                            |
| Type of drive                  | Angetriebene & gezogene Achse |
| Number of bolt holes           | 6                             |
| hub hole diameter [mm].        | 161                           |
| Bolt hole circle diameter [mm] | 205                           |
| Bolt hole diameter [mm]        | 21.5                          |
| Bolt hole design EUWA          | B18 ES 32                     |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R16                           |
| Rim centering                  | BC                            |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Valve seat                     | External Valve                |
| Ventilation holes              | No                            |
| Single / multi-part            | einteilig                     |
| Hump                           | kein Hump                     |
| Cavity Sealed                  | No                            |

---

|                          |             |
|--------------------------|-------------|
| Verschweißung beidseitig | No          |
| Assembly Item no. Valve  | • 47201038  |
| Preassembled valve       | No          |
| TPMS-kompatibles Ventil  | No          |
| Valve hole diameter [mm] | 15.7        |
| Valve design             | Metal valve |
| Valve designation ETRTO  | V5.01.1     |
| Valve length [mm]        | 50.0        |
| Valve angle [°]          | gerade      |