

## WHEELS

Product group	Wheels
Item number	59912690
Valid wheel size	13.0 / 65 - 18
Brand	Alliance
Tread pattern	320
Valid rim size	11 x 18 S
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2800
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15212359
LI / SI / PR	144 A8 / 140 B, 16 PR
Load capacity 1 [kg]	2800
Speed 1 [km/h].	40
Load capacity 2 [kg]	2500
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	61,92
ECE regulation number	ECE 106
Section width (mm)	336

Stat. radius (SLR) [mm]	398
Rolling circumference [mm].	2611
Tread depth (mm)	9,5
E-Ready	No
Assembly Item no. Rim	• 31210145
Load capacity of rim 1 [kg]	4250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3350
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,90
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205

---

Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No