

WHEELS

Product group	Wheels
Item number	59912802
Valid wheel size	650 / 65 R 38
Brand	Alliance
Tread pattern	Forestar 342
Valid rim size	DW 20 B x 38
Rim connection	8/221/275
Offset (mm)	-120
Rim colour	Black
Load capacity complete wheel [kg]	7500
Speed complete wheel [km/h]	10



Technical Informations

Assembly Item no. Tyres	• 15226796
LI / SI / PR	178 A2 / 171 A8
Load capacity 1 [kg]	7500
Speed 1 [km/h].	10
Load capacity 2 [kg]	6150
Speed 2 [km/h].	40
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	498,89
ECE regulation number	ECE 106

Section width (mm)	650
Stat. radius (SLR) [mm]	842
Rolling circumference [mm].	5521
Tread depth (mm)	53,0
Tyre capacity 75% [ltr.]	592.5
E-Ready	No
Assembly Item no. Rim	• 39123154
Load capacity of rim 1 [kg]	6500
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5720
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,60
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS V
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005
Cavity Sealed	No
Forest reinforcement	flange reinforcement Ø19 mm
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	M20

Bolt hole diameter [mm]	24
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No