

WHEELS

Product group	Wheels
Item number	59912925
Valid wheel size	7.50 - 20
Brand	BKT
Tread pattern	AS 504
Valid rim size	5.50 F x 20
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	1250
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15712450
LI / SI / PR	103 A8 / 116 A8, 8 PR
Load capacity 1 [kg]	875
Speed 1 [km/h].	40
Load capacity 2 [kg]	1250
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	51,57
ECE regulation number	ECE 106

Section width (mm)	209
Stat. radius (SLR) [mm]	422
Rolling circumference [mm].	2695
Tread depth (mm)	22,0
Number of lugs	21x2
E-Ready	No
Assembly Item no. Rim	• 32010110
Load capacity of rim 1 [kg]	1500
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,20
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Preassembled valve	No

TPMS-kompatibles Ventil

No
