

## WHEELS

Product group	Wheels
Item number	59912976
Valid wheel size	15.5 / 60 - 18
Brand	BKT
Tread pattern	AT 621
Valid rim size	13 x 18
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	2575
Speed complete wheel [km/h]	10
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15772531
LI / SI / PR	141 A2, 12 PR
Load capacity 1 [kg]	2575
Speed 1 [km/h].	10
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	78,01
ECE regulation number	ECE 106
Section width (mm)	394
Stat. radius (SLR) [mm]	428

Rolling circumference [mm].	2871
Tread depth (mm)	22,5
E-Ready	No
Assembly Item no. Rim	• 32010281
Load capacity of rim 1 [kg]	4250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3350
Speed Rims 2 [km/h]	60
Maximum speed [km/h].	10
Maximum air pressure [bar].	3,00
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve

---

Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade