

WHEELS

Product group	Wheels
Item number	59912985
Valid wheel size	16.0 / 70 - 20
Brand	BKT
Tread pattern	AW 705
Valid rim size	14 x 20
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Red
Load capacity complete wheel [kg]	3450
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15712471
LI / SI / PR	151 A8, 12 PR
Load capacity 1 [kg]	3450
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	83,67
ECE regulation number	ECE 106
Section width (mm)	408
Stat. radius (SLR) [mm]	480

Rolling circumference [mm].	3155
Tread depth (mm)	13,0
E-Ready	No
Assembly Item no. Rim	• 31610340
Load capacity of rim 1 [kg]	3600
Speed Rims 1 [km/h]	30
Load capacity of rim 2 [kg]	3330
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,00
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL3000
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade