

## WHEELS

Product group	Wheels
Item number	59912996
Valid wheel size	16.0 / 70 - 20
Brand	BKT
Tread pattern	AW 705
Valid rim size	14 x 20
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	3450
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15712471
LI / SI / PR	151 A8, 12 PR
Load capacity 1 [kg]	3450
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	83,83
ECE regulation number	ECE 106
Section width (mm)	408
Stat. radius (SLR) [mm]	480

Rolling circumference [mm].	3155
Tread depth (mm)	13,0
E-Ready	No
Assembly Item no. Rim	• 30812500
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3875
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,00
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7

---

Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade