

## WHEELS

Product group	Wheels
Item number	59912998
Valid wheel size	16.0 / 70 - 20
Brand	BKT
Tread pattern	AW 705
Valid rim size	14 x 20
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	4000
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15712472
LI / SI / PR	156 A8, 16 PR
Load capacity 1 [kg]	4000
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	93,08
ECE regulation number	ECE 106
Section width (mm)	408
Stat. radius (SLR) [mm]	480
Rolling circumference [mm].	3155

Tread depth (mm)	13,0
E-Ready	No
Assembly Item no. Rim	• 32010330
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3875
Speed Rims 2 [km/h]	60
Maximum speed [km/h].	40
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

---

Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade