

WHEELS

Product group	Wheels
Item number	59913020
Valid wheel size	16.0 / 70 - 20
Brand	Alliance
Tread pattern	320
Valid rim size	14 x 20
Rim connection	8/221/275
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	3450
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15212480
LI / SI / PR	151 A8 / 147 B, 12 PR
Load capacity 1 [kg]	3450
Speed 1 [km/h].	40
Load capacity 2 [kg]	3075
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	89,64
ECE regulation number	ECE 106
Section width (mm)	418

Stat. radius (SLR) [mm]	465
Rolling circumference [mm].	3140
Tread depth (mm)	13,5
E-Ready	No
Assembly Item no. Rim	• 30812500
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3875
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
