

WHEELS

Product group	Wheels
Item number	59913070
Valid wheel size	385 / 55 R 18
Brand	Alliance
Tread pattern	601
Valid rim size	11 x 18 S
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2500
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15285510
LI / SI / PR	140 A8 / 140 B
Load capacity 1 [kg]	2500
Speed 1 [km/h].	40
Load capacity 2 [kg]	2500
Speed 2 [km/h].	50
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	70,53

ECE regulation number	ECE 106
Section width (mm)	370
Stat. radius (SLR) [mm]	395
Rolling circumference [mm].	2686
Tread depth (mm)	17,0
Tyre capacity 75% [ltr.]	133
E-Ready	No
Assembly Item no. Rim	• 31210145
Load capacity of rim 1 [kg]	4250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3350
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,50
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere

Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade