

## WHEELS

|                                   |               |
|-----------------------------------|---------------|
| Product group                     | Wheels        |
| Item number                       | 59913084      |
| Valid wheel size                  | 365 / 70 R 18 |
| Brand                             | Alliance      |
| Tread pattern                     | 606           |
| Valid rim size                    | 11 x 18       |
| Rim connection                    | 8/221/275     |
| Bolt hole design                  | A3            |
| Rim colour                        | Silver        |
| Load capacity complete wheel [kg] | 2180          |
| Speed complete wheel [km/h]       | 40            |



## Technical Informations

|                            |                |
|----------------------------|----------------|
| Assembly Item no. Tyres    | • 15285030     |
| LI / SI / PR               | 146 A2 / 135 B |
| Load capacity 1 [kg]       | 3000           |
| Speed 1 [km/h].            | 10             |
| Load capacity 2 [kg]       | 2180           |
| Speed 2 [km/h].            | 50             |
| Antistatic                 | No             |
| Tyre colour                | Black          |
| Nettogewicht [kg] (gültig) | 88,89          |
| ECE regulation number      | not necessary  |
| Section width (mm)         | 400            |

|                                |                               |
|--------------------------------|-------------------------------|
| Stat. radius (SLR) [mm]        | 440                           |
| Rolling circumference [mm].    | 2902                          |
| Tread depth (mm)               | 22,0                          |
| E-Ready                        | No                            |
| Assembly Item no. Rim          | • 31612155                    |
| Load capacity of rim 1 [kg]    | 3650                          |
| Speed Rims 1 [km/h]            | 40                            |
| Maximum speed [km/h].          | 40                            |
| Maximum air pressure [bar].    | 3,75                          |
| Type of drive                  | Angetriebene & gezogene Achse |
| Hump                           | kein Hump                     |
| Valve protection               | VS H                          |
| Single / multi-part            | einteilig                     |
| Rim material                   | steel                         |
| RAL                            | RAL9006                       |
| Cavity Sealed                  | No                            |
| Ventilation holes              | No                            |
| Verschweißung beidseitig       | No                            |
| Rim centering                  | BC                            |
| Number of bolt holes           | 8                             |
| Bolt hole design EUWA          | B22 ES 36                     |
| Bolt hole diameter [mm]        | 27                            |
| Countersinking                 | Sphere                        |
| Spherical countersink [mm].    | R18                           |
| hub hole diameter [mm].        | 221                           |
| Bolt hole circle diameter [mm] | 275                           |
| Valve seat                     | External Valve                |

---

|                          |             |
|--------------------------|-------------|
| Valve hole diameter [mm] | 15.7        |
| Preassembled valve       | No          |
| Valve design             | Metal valve |
| Valve designation ETRTO  | V5.01.1     |
| Valve length [mm]        | 50.0        |
| Valve angle [°]          | gerade      |