

## WHEELS

Product group	Wheels
Item number	59913105
Valid wheel size	405 / 70 R 18
Brand	Alliance
Tread pattern	608
Valid rim size	13 x 18
Rim connection	8/221/275
Bolt hole design	B3
Offset (mm)	+40
Rim colour	Silver
Load capacity complete wheel [kg]	3650
Speed complete wheel [km/h]	50



## Technical Informations

Assembly Item no. Tyres	• 15284900
LI / SI / PR	153 A2 / 141 B
Load capacity 1 [kg]	3650
Speed 1 [km/h].	10
Load capacity 2 [kg]	2575
Speed 2 [km/h].	50
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	89,16
ECE regulation number	ECE 106

Section width (mm)	408
Stat. radius (SLR) [mm]	450
Rolling circumference [mm].	3084
Tread depth (mm)	18,5
Tyre capacity 75% [ltr.]	141
E-Ready	No
Assembly Item no. Rim	• 33060096
Load capacity of rim 1 [kg]	3750
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3150
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	50
Maximum air pressure [bar].	3,75
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere

---

Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade