

WHEELS

Product group	Wheels
Item number	59913125
Valid wheel size	500 / 70 R 24
Brand	Alliance
Tread pattern	Agro Industrial 580
Valid rim size	DW 16 L x 24
Rim connection	10/281/335
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	5000
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15285321
LI / SI / PR	164 A8 / 164 B
Load capacity 1 [kg]	5000
Speed 1 [km/h].	40
Load capacity 2 [kg]	5000
Speed 2 [km/h].	50
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	177,28
ECE regulation number	ECE 106
Section width (mm)	505

Stat. radius (SLR) [mm]	600
Rolling circumference [mm].	3900
Tread depth (mm)	40,0
E-Ready	No
Assembly Item no. Rim	• 39122900
Load capacity of rim 1 [kg]	6080
Speed Rims 1 [km/h]	65
Maximum speed [km/h].	50
Maximum air pressure [bar].	4,00
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7

Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade