

## WHEELS

Product group	Wheels
Item number	59913260
Valid wheel size	12.4 - 24
Brand	Alliance
Tread pattern	357
Valid rim size	W 10 x 24
Rim connection	6/161/205
Bolt hole design	B2
Rim colour	Silver
Load capacity complete wheel [kg]	1800
Speed complete wheel [km/h]	40



Bohnenkamp  
■ ■ ● Moving Professionals

 **ALLIANCE**  
ENGINEERED TO KEEP YOU AHEAD

## Technical Informations

Assembly Item no. Tyres	• 15222197
LI / SI / PR	129 A8, 12 PR
Load capacity 1 [kg]	1850
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	81,32
ECE regulation number	ECE 106
Section width (mm)	315
Stat. radius (SLR) [mm]	533
Rolling circumference [mm].	3461

Tread depth (mm)	34,0
Number of lugs	18x2
E-Ready	No
Assembly Item no. Rim	• 63035201
Load capacity of rim 1 [kg]	2100
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	1800
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,50
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No