

WHEELS

Product group	Wheels
Item number	59913263
Valid wheel size	9.5 - 24
Brand	BKT
Tread pattern	TR 135
Valid rim size	W 8 x 24
Rim connection	6/161/205
Bolt hole design	B2
Rim colour	Silver
Load capacity complete wheel [kg]	1250
Speed complete wheel [km/h]	30
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15722096
LI / SI / PR	116 A6 / 112 A8, 10 PR
Load capacity 1 [kg]	1250
Speed 1 [km/h].	30
Load capacity 2 [kg]	1120
Speed 2 [km/h].	40
Direction	Left
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	70,88

ECE regulation number	ECE 106
Section width (mm)	241
Stat. radius (SLR) [mm]	502
Rolling circumference [mm].	3234
Tread depth (mm)	30,5
E-Ready	No
Assembly Item no. Rim	• 31612730
Load capacity of rim 1 [kg]	1500
Speed Rims 1 [km/h]	30
Maximum speed [km/h].	30
Maximum air pressure [bar].	3,50
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve

Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No