

## WHEELS

Product group	Wheels
Item number	59913292
Valid wheel size	500 / 45 - 20
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	16 x 20
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	3075
Speed complete wheel [km/h]	40



## Technical Informations

Assembly Item no. Tyres	• 15212563
LI / SI / PR	134 A8 / 147 A8, 12 PR
Load capacity 1 [kg]	2120
Speed 1 [km/h].	40
Load capacity 2 [kg]	3075
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	109,39
ECE regulation number	ECE 106
Section width (mm)	490

Stat. radius (SLR) [mm]	433
Rolling circumference [mm].	2820
Tread depth (mm)	26,0
E-Ready	No
Assembly Item no. Rim	• 31610602
Load capacity of rim 1 [kg]	4750
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	50
Maximum air pressure [bar].	2,80
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205

---

Valve seat	External Valve
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade